

## Notched Turned Back Nipples

### Features

- When used with an appropriate notched ferrule, these fittings can be swaged or crimped onto hose providing improved shank retention
- When used with double bolt or band clamps, notched turn back nipples provide shank retention similar to that of the King® turned back nipples
- The stem can be removed from a damaged hose by cutting away the ferrule without necessarily damaging the fitting
- For use with lap joint flanges on page 970

Special pushers required:

1-1/2" stem – RN150NOPUSH

2" stem – RN200NOPUSH

2-1/2" stem – RN250NOPUSH

3" stem – RN300NOPUSH



Size	316 Stainless Steel Part #
1-1/2"	RN150NO
2"	RN200NO
3"	RN300NO

NOTE: For additional information on pipe dimensions please reference [dixonvalve.com](http://dixonvalve.com).

## Notched Ferrules

### Features

- Reference notched shanks above and adapters on page 45
- Dixon stems and ferrules are specifically designed to be used together as a coupling system; due to differences in dimensions and tolerances for safety reasons, do not use other manufacturers' stems or ferrules with Holedall® products



Hose I.D.	Hose O.D.		304 Stainless Steel Part #
	From	To	
1-1/2"	1-60/64"	2-12/64"	GAS2334NO
	2-4/64"	2-22/64"	GAS2370NO
2"	2-30/64"	2-44/64"	GAS2709NO
	2-42/64"	2-54/64"	GAS2885NO
2-1/2"	2-54/64"	3"	GAS3012NO
3"	3-30/64"	3-46/64"	GAS3760NO
	3-47/64"	3-54/64"	GAS3885NO
4"	4-40/64"	4-47/64"	GAS5010NO



NOTE: King Crimp® fittings, ferrules, and sleeves can be found on pages 5 - 17.