

Type B

Male with Machined Hose Shank


Features

- Dixon® combination nipple style hose shank machined from Schedule 40 pipe
- Recommended for use with steel King Crimp® sleeves



| Size | Galvanized Steel Part # |
|------|-------------------------|
| 3" | MC3093ST35 |
| 4" | MC3094ST40 |
| 6" | MC3096ST60 |

Male x 150# ASA Flange



| Size | Galvanized Steel Part # |
|------|-------------------------|
| 4" | MC3134 |
| 6" | MC3136 |
| 8" | MC3138 |
| 10" | MC31310 ¹ |
| 12" | MC31312 ¹ |

¹ 10" and 12" supplied with ACB304 lever assist bar on page 397

NOTE: For flange dimensions, diagrams, and additional information please reference dixonvalve.com.


Male Weld-On



| Size | Unplated Steel Part # |
|------|-----------------------|
| 2" | 3032 |
| 3" | 3033 |
| 4" | 3034 |
| 6" | 3036 |
| 8" | 3038 |
| 10" | 30310 |
| 12" | 30312 |

NOTE: Female and male fittings are commonly used for butt-welding to pipe

Heavy Duty Female x Dixon Combination Nipple Hose Shank



| Size | Galvanized Steel Part # |
|------|-------------------------|
| 3" | FC3103ST35 |
| 4" | FC3104ST40 |
| 6" | FC3106ST60 |

G