


### Mini Spray Nozzle



**Features**

- 1/2" female NPT inlet
- Do not use with steam lines 
- Designed as an industrial lightweight nozzle with heavyweight performance
- Durable dark blue cover protects user from hot surfaces produced by high temperature wash down applications
- Reduces hand fatigue and provides smooth lever action
- Variable spray patterns from fan spray to solid stream
- Drip-free automatic shutoff feature

**Specifications**

- Pressure rating **150 PSI** at **200°F (93°C)**
- Flow: **9.6 GPM** at 100 PSIG

**Stainless Steel**  
**Part #**

DM150SDB

H

### Spray Nozzle



**Features**

- 1/2" female NPT inlet
- Designed to prevent accidental spray
- Durable dark blue cover prevents front-mounted lever from being accidentally activated if nozzle is dropped
- Reduces hand fatigue and provides smooth lever action
- Trigger locking mechanism provides safe and secure method of keeping the nozzle open during any spray pattern
- Variable spray patterns from fan spray to solid stream
- Drip-free automatic shut-off feature
- Can be used with D150S-WAND

**Specifications**

- Rated to **150 PSI** at **200°F (93°C)**
- **9.6 GPM** flow capacity at 100 PSIG


**Stainless Steel**  
**Part #**

D150SDB

### Washdown Wand



**Features**

- Designed to provide user with a means of reaching desired washdown locations previously deemed unreachable by extending the nozzle by 3'
- Adjustable spray tip can be changed from fan to solid spray by twisting the tip until the desired flow pattern is achieved
- Quick disconnect feature allows user to quickly connect wand to the nozzle above
- Designed to only fit the D150SDB nozzle
- Wand is not for use with steam 

**Specification**

- Minimum pressure is **75 PSI**

**300 Series Stainless Steel**  
**Part #**

D150S-WAND