

Straight GHT Valve

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**



Powder-coated Zinc Part #

GHV

GHT Ball Valve

Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**
- Reduced port



Description

Forged Brass Part #

3/4" female x 3/4" male GH

500GHV

GHT Twin Valve

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**



Powder-coated Zinc Part #

GHYV

Garden Hose Y Valve

Feature

- Double Y valve, swivel inlet – with Higbee cut threads (capped) to prevent cross threading

Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**



Description

Forged Brass Part #

3/4" female x double 3/4" male GH

500GHY

Garden Hose Y Coupler

Specifications

- Maximum working pressure: **100 PSI**
- Maximum temperature: **140°F (60°C)**



Description

Nickel-plated Forged Brass Part #

3/4" female x double 3/4" male GH

500YCF

GHT Y

Feature

- Includes one end cap

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**



Powder-coated Zinc Part #

GHY