

## Hose Fittings

### Brass Ferrules for Air and Fluid

**Feature**

- Sold in package quantities only



BFM



BFL

Ferrule I.D.	Ferrule Length	End Hole Size	Metal Gauge	Std Ind Part #	Bore/Crimp Diameter <sup>1</sup>	Previous Part #	Brass Part #	Pkg Qty
.478"	.688"	.328"	.024"	4750	0.450	2004750C	BFM478	50
.500"	1"	.344"	.024"	7322	0.475	2005005C	BFM500	50
.528"	1"	.375"	.024"	7323	0.500	2005255C	BFM525	50
.528"	1"	.438"	.024"	7324	0.500	2005310C	BFM531	50
.562"	1"	.438"	.024"	7325	0.525	2005620C	BFM562	50
.593"	1"	.438"	.024"	7326	0.550	2005930C	BFM593	50
.625"	1"	.438"	.024"	7327	0.575	2006255C	BFM625	50
.656"	1"	.438"	.024"	7328	0.600	2006560C	BFM656	50
.687"	1"	.500"	.024"	7329	0.625	2006900C	BFM687	50
.718"	1"	.625"	.024"	7330	0.675	2007180C	BFM718	50
.718"	1"	.500"	.024"	7330B	0.675	---	BFM718B	50
.750"	1"	.625"	.024"	7331	0.700	2007505C	BFM750	50
.750"	1"	.500"	.024"	7331B	0.700	---	BFM750B	50
.781"	1"	.625"	.024"	7332	0.725	2007810C	BFM781	50
.781"	1"	.500"	.024"	7332B	0.725	---	BFM781B	50
.812"	1"	.625"	.024"	7333	0.750	2008120C	BFM812	50
.380"	.500"	.266"	.016"	622	0.350	---	BFL380	50
.400"	.469"	.266"	.020"	619	0.375	2004000C	BFL400	50
.410"	.500"	.266"	.016"	620	0.375	---	BFL410	50
.450"	.469"	.344"	.016"	769	0.425	2004530C	BFL450	50
.500"	.500"	.344"	.016"	624	0.450	2005000C	BFL500	50
.525"	.500"	.344"	.016"	625	0.475	2005250C	BFL525	50
.548"	.484"	.375"	.016"	626	0.500	2005500C	BFL548	50
.564"	.750"	.375"	.019"	3588	0.525	---	BFL564	50
.575"	.484"	.469"	.019"	KK	0.525	---	BFL575	50
.600"	.500"	.500"	.019"	JJ	0.550	---	BFL600	50
.625"	.500"	.500"	.019"	II	0.575	2006250C	BFL625	50
.650"	.500"	.500"	.019"	HH	0.600	2006500C	BFL650	50
.675"	.516"	.500"	.019"	GG	0.625	2006750C	BFL675	50
.725"	.531"	.500"	.019"	EE	0.675	2007250C	BFL725	50
.750"	.531"	.500"	.019"	DD	0.675	2007500C	BFL750	50
.775"	.531"	.500"	.016"	CC	0.700	2007750C	BFL775	50

<sup>1</sup> Plain die bore diameter can be used as crimp spec ±.005

NOTE: For use with crimpers and ribbed and plain dies on pages 447-450

### Brass Ferrules for Fluid

**Feature**

- Sold in package quantities only



BFMW

Ferrule I.D.	Ferrule Length	End Hole Size	Metal Gauge	Std Ind Part #	Ribbed Die*	Plain Die*	Bore/Crimp Diameter <sup>1</sup>	Previous Part #	Brass Part #	Pkg Qty
.800"	.844"	.688"	.024"	---	R28	P29	0.750	---	BF800	25
.825"	.844"	.688"	.024"	---	R27	P28	0.775	---	BF825	25
.850"	.563"	.688"	.019"	Z	R26	P27	0.800	---	BF850	25
.875"	.844"	.688"	.024"	7244A	R25	P26	0.825	2008750C	BFW875	25
.900"	.844"	.688"	.024"	5029A	R24	P25	0.850	---	BFW900	25
.937"	.844"	.688"	.024"	7242A	R23	P24	0.875	2009250C	BFW925	25
.975"	.844"	.688"	.024"	5028A	R21	P22	0.925	2009750C	BFW975	25
1.025"	.844"	.693"	.024"	7114A	R19	P20	0.975	2001025C	BFW1025	25
1.175"	.844"	.875"	.024"	7088A	R13	P14	1.125	2001175C	BFW1175	25
1.050"	.625"	.750"	.025"	3605	R18	P19	1.000	---	BFMW1050	25
1.100"	.844"	.812"	.024"	5027A	R16	P17	1.050	2001100C	BFMW1100	25
1.150"	.844"	.875"	.024"	7104A	R15	P15	1.100	2009950C	BFMW1150	25
1.225"	.875"	.875"	.025"	875-K	R11	P12	1.175	2001225C	BFMW1225	25
1.275"	.875"	1.000"	.025"	875-I	R9	P10	1.225	---	BFMW1275	25
1.400"	.687"	1.125"	.019"	D	R4	P5	1.350	---	---	25
1.500"	.875"	1.125"	.025"	1500	---	P1	1.450	2001500C	BFMW1500	25

<sup>1</sup> Plain die bore diameter can be used as crimp spec ±.005

NOTE: For use with crimpers and ribbed and plain dies on pages 447-450