


Type E Adapters with Notched NOS Shank

Adapter and Shank

B

Features

- The system allows improved inventory management by stocking one stem and two ferrules, and cover the same hose range with less inventory. You must purchase a fitting and the matching ferrule to create an assembly.
- For hose outside diameters of 2-4/64" and below, the couplings are crimp only 
- For hose outside diameters of 2-5/64" and above, the couplings can be crimped or swaged
- For use with notched ferrules on page 44
- See page 374 for male NPT notched NOS fittings



Size	316 Stainless Steel Part #
2"	200ENOSSS ¹
3"	300ENOSSS ¹

Only use the NOS shank with the NOS ferrules.

Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturers' stems or ferrules with Dixon® products. 

¹ Part will be discontinued as stock is depleted

Notched NOS Ferrules

Size	Hose O.D.		304 Stainless Steel Part #
	From	To	
1-1/2"	1-60/64"	2-12/64"	GAS2334NOS
	2-4/64"	2-22/64"	GAS2370NOS
2"	2-30/64"	2-44/64"	GAS2709NOS
	2-42/64"	2-54/64"	GAS2885NOS
3"	3-30/64"	3-46/64"	GAS3760NOS
	3-47/64"	3-54/64"	GAS3885NOS



NOTE: Reference notched shanks on page 374 and adapters above