


Hydraulic Adapters – 37° JIC

Male x Male

Specifications

- Reference SAE 070101
- Pressure rating at 70°F (21°C)




Male JIC 37°	Male JIC 37°	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	1204-04-04
9/16" – 18	9/16" – 18		1204-06-06
3/4" – 16	7/16" – 20	4500	1204-08-04
	3/4" – 16		1204-08-08
7/8" – 14	3/4" – 16	3500	1204-10-08
	7/8" – 14		1204-10-10
1-1/16" – 12	3/4" – 16		1204-12-08
	7/8" – 14		1204-12-10
	1-1/16" – 12		1204-12-12
1-5/16" – 12	1-1/16" – 12		3000
	1-5/16" – 12	1204-16-16	
1-5/8" – 12	1-5/8" – 12	2500	1204-20-20
1-7/8" – 12	1-7/8" – 12	2000	1204-24-24

Male Flare x Male NPTF

Specifications

- Reference SAE 070102
- Pressure rating at 70°F (21°C)

K



Male JIC 37° Flare	Male NPTF	PSI	Zinc Plated Steel Part #	316 Stainless Steel Part #
7/16" – 20	1/8" – 27	4500	2404-4-2	---
	1/4" – 18		2404-4-4	SS2404-4-4
	3/8" – 18	4000	2404-4-6	---
	1/2" – 14	3000	2404-4-8	---
1/2" – 20	1/8" – 27	4000	2404-5-2	---
	1/8" – 27		2404-6-2	---
9/16" – 18	1/4" – 18		2404-6-4	---
	3/8" – 18		2404-6-6	SS2404-6-6
	1/2" – 14		3000	2404-6-8
3/4" – 16	1/4" – 18		4000	2404-8-4
	3/8" – 18	2404-8-6		---
	1/2" – 14	3000	2404-8-8	SS2404-8-8
	3/4" – 14	2500	2404-8-12	---
7/8" – 14	1/2" – 14	3000	2404-10-8	---
	3/4" – 14	2500	2404-10-12	---
1-1/16" – 12	1/2" – 14	3000	2404-12-8	---
	3/4" – 14	2500	2404-12-12	SS2404-12-12
	1" – 11-1/2	2000	2404-12-16	---
1-5/16" – 12	3/4" – 14	2500	2404-16-12	---
	1" – 11-1/2	2000	2404-16-16	SS2404-16-16
1-5/8" – 12	1-1/4" – 11-1/2	1150	2404-20-20	---
1-7/8" – 12	1-1/2" – 11-1/2	1000	2404-24-24	---
2-1/2" – 12	2" – 11-1/2		2404-32-32	---

Male Flare x Female NPTF

Specifications

- Reference SAE 070103
- Pressure rating at 70°F (21°C)



Male JIC 37° Flare	Female NPTF	PSI	Zinc Plated Steel Part #	316 Stainless Steel Part #
7/16" – 20	1/8" – 27	4500	2405-4-2	---
	1/4" – 18		2405-4-4	SS2405-4-4
9/16" – 18	1/4" – 18	4000	2405-6-4	---
	3/8" – 18		2405-6-6	SS2405-6-6
	1/2" – 14	3000	2405-6-8	---
3/4" – 16	3/8" – 18	4000	2405-8-6	---
	1/2" – 14	3000	2405-8-8	SS2405-8-8
7/8" – 14	3/4" – 14	2500	2405-8-12	---
	1/2" – 14	3000	2405-10-8	---
1-1/16" – 12	3/4" – 14	2500	2405-12-12	SS2405-12-12
	1" – 11-1/2	2000	2405-12-16	---
1-5/16" – 12	1" – 11-1/2		2405-16-16	SS2405-16-16
1-5/8" – 12	1-1/4" – 11-1/2	1150	2405-20-20	---