

## Hydraulic Adapters – NPTF

### Features


- Compact design provides ease of assembly in confining areas
- Designed to prevent hose stress due to twisting during assembly
- Female NPSM swivel seals on a 30° seat
- Male NPTF must have a 30° chamfer to seal

### Male x Female NPSM Swivel Adapters

#### Specifications

- Reference SAE 140130
- Pressure rating at **70°F (21°C)**

Male NPTF	Female NPSM Swivel	PSI	Zinc Plated Steel Part #
1/8" - 27	1/8" - 27	5000	1404-2-2
	1/4" - 18		1404-2-4
1/4" - 18	1/4" - 18	4500	1404-4-4
	3/8" - 18		1404-4-6
3/8" - 18	1/4" - 18	4000	1404-6-4
	3/8" - 18		1404-6-6
	1/2" - 14		1404-6-8
1/2" - 14	3/8" - 18	3000	1404-8-6
	1/2" - 14		1404-8-8
	3/4" - 14		1404-8-12
3/4" - 14	1/2" - 14	2500	1404-12-8
	3/4" - 14		1404-12-12
1" - 11-1/2	1" - 11-1/2	2000	1404-16-16
1-1/4" - 11-1/2	1-1/4" - 11-1/2	1150	1404-20-20
1-1/2" - 11-1/2	1-1/2" - 11-1/2	1000	1404-24-24
2" - 11-1/2	2" - 11-1/2		1404-32-32




### Female Hex Pipe Couplings

#### Specifications

- Reference SAE 140138
- Pressure rating at **70°F (21°C)**

Female NPTF	Female NPTF	PSI	Zinc Plated Steel Part #
1/8" - 27	1/8" - 27	5000	5000-2
1/4" - 18	1/4" - 18		5000-4
3/8" - 18	1/4" - 18	4000	5000-6-4
	3/8" - 18		5000-6
1/2" - 14	3/8" - 18	3000	5000-8-6
	1/2" - 14		5000-8
3/4" - 14	3/4" - 14	2500	5000-12
	3/4" - 14		5000-16-12
1" - 11-1/2	1" - 11-1/2	2000	5000-16
	1" - 11-1/2		5000-16
1-1/4" - 11-1/2	1-1/4" - 11-1/2	1150	5000-20



### Female x Female NPSM Swivel Nuts

#### Specifications

- Reference SAE 140131
- Pressure rating at **70°F (21°C)**

Female NPTF	Female NPSM Swivel	PSI	Zinc Plated Steel Part #
1/8" - 27	1/8" - 27	5000	1405-2-2
1/4" - 18	1/4" - 18	4500	1405-4-4
	1/4" - 18		1405-6-4
3/8" - 18	3/8" - 18	4000	1405-6-6
	1/2" - 14		1405-6-8
1/2" - 14	1/2" - 14	3000	1405-8-8
	1/2" - 14		1405-12-8
3/4" - 14	3/4" - 14	2500	1405-12-12
	3/4" - 14		1405-12-12
1" - 11-1/2	1" - 11-1/2	2000	1405-16-16
1-1/4" - 11-1/2	1-1/4" - 11-1/2	1150	1405-20-20
1-1/2" - 11-1/2	1-1/2" - 11-1/2	1000	1405-24-24
2" - 11-1/2	2" - 11-1/2		1405-32-32

