



Bumpered Fog Nozzles

Features

- Basic spray nozzle, capable of straight stream and fog spray pattern
- Twist shut-off and spray pattern change
- Supplied with a bumper

Specification

- Maximum rated pressure: **175 PSI**



BBN75

Size	Thread	Rated Flow at Wide Open: GPM at 100 PSI	FM/UL/ULC Listed for class A and B Fires Brass Part #	Unlisted Brass Part #
3/4"	GHT	51	BBN75GHT	BBN75GHT-NL ^{1,2}
	NPSH		BBN75	BBN75-NL ^{1,2}
1"	NPSH	54	BBN100	BBN100-NL ^{1,2}
	NST		BBN100NST	BBN100NST-NL ^{1,2}

¹ Not UL listed

² Not Factory Mutual approved

NOTE: Replacement washers can be found on page 782

Industrial Fog Nozzles



BFN150



BFN200

Features

- Delivers 30°, 60°, and 90° fog pattern – shut-off – straight stream – fog
- Supplied with bumper

Specification

- Maximum rated pressure: **175 PSI** (water only) at 70°F (21°C)

Size	Thread	Rated Flow at Wide Open: GPM at 100 PSI	FM and UL Listed for class A and B Fires (except noted ^{1,2}) Brass Part #	Unlisted Brass Part #
1-1/2"	NPSH	97	BFN150	BFN150-NL ^{1,2}
2"			BFN150NST	BFN150NST-NL ^{1,2}
2-1/2"		---	BFN250 ²	BFN250-NL ^{1,2}
2-1/2"	NST (NH)	205	BFN250NST ²	BFN250NST-NL ^{1,2}

¹ Not UL listed

² Not Factory Mutual approved

NOTE: Replacement washers can be found on page 782.

N