

### SSA – Storz x Storz Adapter

**Materials**

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5" and 6"

**Specification**

- Working pressure: 150 PSI at 70°F (21°C)

Storz Size	Storz Size	6061-T6 Forged Aluminum Part #
1-1/2"	2"	SSA1520
	2-1/2"	SSA1525
2"	2-1/2"	SSA2025
	3"	SSA2030
	4"	SSA2540
4"	5"	SSA4050
	6"	SSA4060
5"		SSA5060



### SSA30 – Storz x Storz 30° Elbow Adapters

**Materials**

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5" and 6"

**Specification**

- Working pressure: 150 PSI at 70°F (21°C)

Storz Size	Storz Size	6061-T6 Forged Aluminum Part #
5"	5"	SSA30-550



### Storz Fire Department Connections

**Features**

- Designed to work with 5" Storz universal connections
- UL approved screen helps to keep debris out of the line
- Flat-faced flange
- Comes with vented cap and cable

**Specification**

- Maximum working pressure: 250 PSI at 70°F (21°C)

**Approval**

- Screen is UL approved



**With Screen**

Storz Size	Female	Part #
5"	BSP	FDCS500BS



**Without Screen**

Storz Size	Female	Aluminum Part #
5"	BSP	FDC500BS

