



Two-Way Male Outlet – Roof Connections

Application

- Used to create roof connections, fire pump test connections, wall hydrants or sidewalk (free standing) hydrants

Feature

- Other configurations are available, contact Dixon® for additional information

Specifications

- Maximum operating pressure: **175 PSI at 70°F (21°C)**
- Provides **250 GPM** minimum per outlet

Approval

- UL listed

Back Outlet




| Pipe Size | (2) Outlets Male | Cast Brass Part # |
|-----------|------------------|-----------------------|
| 4" | 2-1/2" NPT | IRC4025 ¹ |
| | | FRC4025 |
| | 2-1/2" NST (NH) | IRC4025F ¹ |
| | | FRC4025F |
| 6" | 2-1/2" NPT | FRC6025 |
| | 2-1/2" NST (NH) | FRC6025F |

| Groove Size | (2) Outlets Male | Cast Brass Part # |
|-------------|------------------|------------------------|
| 4" | 2-1/2" NST (NH) | IRC4025GF ¹ |

¹ Import

Dimensions



| Size | A | B | C |
|----------------------|---------|---------|--------|
| 4" x 2-1/2" x 2-1/2" | 7-7/8" | 5-3/16" | 5-1/4" |
| 6" x 2-1/2" x 2-1/2" | 8-3/16" | 6-3/8" | 7-5/8" |

N